

## How to upgrade diagun

1 取出 diagun的程序卡

Take out diagun SD card




2连接程序卡到电脑 Insert

SD card into computer







3保存好 diagun老版本的程序【备用】 Save the old software and program for immediate use




4找到升级程序===解压升级程序 Find out the upgrade software and then decompress it



5找到解压好的升级程序 GAG文件=====拷贝到 diagun的程序卡里面 Open “GAG” file in the decompressed upgrade software, then copy and paste it into the SD card.







6程序拷贝完成后就取出 diagun的程序卡 =====插入 diagun主机=====蓝牙主机连接车点击  
蓝牙图标进入诊断程序

After finishing paste the software, take out diagun SD card and then insert it into diagun main unit. Next, connect Bluetooth Device to car, then the Bluetooth Device displays on the Diagun screen, click it and enter the diagnosis operation interface.




7选择连接要诊断车 vw=== 点击 ok Select the car models you want to diagnose and then click **OK**






8 进入诊断车型的软件版本==点 ok Enter diagnosing vehicles models software version and then click **OK**




9软件启动=====与车辆通讯请等待 The software starts and communicating with the vehicle, please wait...




10 Diagun与车辆连接完成 ==读出车辆的信息 Diagun finishes communicating with vehicles and read out vehicle information





11读取故障代码 Reading  
fault codes (DTCs)



12故障代码读取成功 Successfully read  
out fault codes (DTCs)

Diagnostic Trouble code		
Fault code	Fault code description	State
16885	P0501 Vehicle speed sensor A:range/performance	
17978	P1570 Engine control module disabled	
16556	P0172 system too rich bank 1	sporadic:
16514	P0130 O2 Sensor circuit, Bank 1-sensor 1:Malfunction	sporadic:
17564	P1156 Manifold absolute pressure (MAP) sensor circuit-G71:open/sh	

升级成功!

Upgrade successfully